

www.rhopointinstruments.com

103.5 103.8 104.7

IOPOIL VO.GLOSS

NO

26/01/17 17:04

RHOPOINT NOVO-GLOSS TRIO

- LOW COST triple angle Glossmeter
- Lightweight and portable
- Fully featured instrument
- BT wireless data transfer



Measurement

Fast measurement of all parameters. Full on-board statistics with graphical trend analysis and reporting.



Simultaneous measurement of all parameters, results are date and time stamped.

Statistics 1 📃 🛓								
∢ ∰ ▶	GRAPH		n=5					
	20°	60°	85°					
	99.3	98.9	98.1					
Max	99.4	99.0	98.1					
Min	99.3	98.9	98.1					
Mean	99.4	99.0	98.1					
SD	0.0	0.0	0.0					

Displays full statistics for the number of readings in the current batch.



Graphical reporting for quick trend analysis.



Pass / fail parameters can be defined for instant identification of non-conformances.

Easy Batching

User definable batch names and batch sizes for quicker and more efficient reporting.



Rapid data transfer



Software-free data transfer.

USB connection to PC instantly recognises the device as a drive location which facilitates the quick transfer of files using Windows Explorer or similar.


Direct data input via BT wireless



Instantly transmit measured readings directly to programs such as MS Excel on your PC / tablet to greatly simplify the reporting process.

	1	2	3	4	5	6
DATE	22/02/2013	22/02/2013	22/02/2013	22/02/2013	22/02/2013	22/02/2013
TIME	11:16:24	11:16:42	11:17:17	11:17:37	11:17:58	11:18:19
20°	30.8	32.3	28.4	35.1	34.6	28
60°	70.1	71.8	68.3	73.8	73.2	68.3
85°	88.9	89.1	87.8	90.4	90.4	87.5
Calibrated	22/02/2013	22/02/2013	22/02/2013	22/02/2013	22/02/2013	22/02/2013
Serviced	19/02/2013	19/02/2013	19/02/2013	19/02/2013	19/02/2013	19/02/2013
S/N	2000728	2000728	2000728	2000728	2000728	2000728

Statistical analysis via Novo-Gloss Multi Gauge Software



This software provides an easy means to measure, import and compare data and export the measurements into several other file formats, e.g. PDF, Excel[®] or CSV.

LOW COST GLOSSMETER

SAMPLE APPLICATIONS



Paints and Coatings



Printing Ink



Powder Coating



Plastics Industry



Automotive Re-finish



Furniture



Metal Polishers



```
Measurement range:
                                                    Resolution:
                                                                                0.1 GU
                                                    Repeatability:
                                                    Reproducibility:
                                                    Standards:
Polished Stone
```



Automotive Detailing



Smartphone, Tablet PC and Laptop Covers



Printed Cartons



Yacht Manufacturers

SPECIFICATIONS



Improved accuracy and resolution on high gloss & metallic samples (>70GU when measured at 60°) Measurement range: 0-2000 GU

60°

85°

Improved resolution for matt finishes (<10GU when measured at 60°) Measurement range: 0-199 GU

Universal angle - all gloss levels

Measurement range: 0-1000 GU

0-100 GU 100-2000 GU 0.1 GU ±0.2 GU ±0.2 % ±0.5 % ±0.5 GU ISO 2813, ISO 7668 ASTM D523, ASTM D2457 DIN 67530 JIS Z 8741, JIS K 5600-4-7



RHOPOINT **NOVO-GLOSS** TRIO

INSTRUMENT SPECIFICATIONS

Operation

- Full colour easy to read screen
- L Adjustable brightness
- 6 button touch sensitive interface

Construction

Integrated calibration holder with in-position detector for error free calibration

Measurement

- Single button push to measure all parameters
- Fast measurement
- L Results batching with user definable names

Statistical Analysis

Max, min, mean, S.D.

Graphical Analysis

- On board trend analysis
- Gloss values

Power

- L Rechargeable lithium ion
- L 17+ hours operation
- 10,000+ readings per charge

Memory

- 8MB= >2000 readings
- User defineable alphanumeric batching

Data Transfer

- BT wireless
- L PC compatible
- USB connection, no software install required

Measurement Area

- 20°: 6mm x 6.4mm
- 60°: 6mm x 12mm
- 85°: 4.4mm x 44mm
- Operating Temperature: 15 - 40 ° C (60 - 104 ° F)
- Humidity: Up to 85%, non condensing

Dimensions & Weight

- 65mm x 140mm x 50mm (H x W x D)
- Weight: 390g
- Packed weight: 1.6kg
- L Packed dimensions: 110mm x 280mm x 220mm (H x W x D)
- Commodity code: 9027 5000

Languages



INCLUDED ACCESSORIES

- Certified calibration tile with certificate
- USB data cable
- Wrist strap
- L Novo-Gloss Multi Gauge Software
- USB data stick
 - Instruction manual
 - BT wireless data app
 - Example Excel spreadsheets
- Instructional videos

EXTRAS

FREE EXTENDED WARRANTY - please register your product at http://www.rhopointinstruments.com/instrument-registration

FREE LIGHT SOURCE WARRANTY

Guaranteed for the life of the instrument

CALIBRATION AND SERVICE

Fast and economic service via our global network of accredited calibration and service centres. Please visit www.rhopointinstruments.com/support for detailed information.





ISO 9001:2008

00640/02/17



Rhopoint Instruments Limited • Rhopoint House Enviro 21 Park • Queensway Avenue South • St Leonards-on-Sea East Sussex • TN38 9AG • UK • Tel: +44 (0) 1424 739622 sales@rhopointinstruments.com • www.rhopointinstruments.com